

CT2000 KVA

Genset Power Output

Name	Voltage	Speed	P.F.	Prime Rating*	Standby rating
CT2000	220-380 V	1500-50Hz	0.8	2045 kva	2250 kva

* The prime power rating of the generating set is for unlimited hours usage with variable load usually between 70% & 80 % of prime rate. Noting that a 10% overload is available for 1 hour every 12 hours operation

Engine Technical Data

Model	Cummins QSK60G4/G6
Cylinders	16 Vee type
Aspiration	Turbocharged, Aftercooled
Combustion	Direct injection
Cooling system	Water Cooled
Displacement	60.2 L
Lube oil Capacity	280 L
Coolant Capacity	490 L
Governor	Electronic
No. of Cycles	4
Speed	1500 rpm
Radiator Cooling Air Flow @ 50Hz	34 m ³ /sec



Alternator Technical Data

Regulation	± 0.5%
International protection	IP23
Insulation class	H
Terminals	6
Frequency	50Hz
Cooling Air Flow @ 50 Hz	2.7 m ³ /sec

Fuel Consumption (L/Hr)

	50Hz
at 100% Load	394.00
at 75% Load	291.00
at 50% Load	200.00
at 25% Load	114.00

Genset Shipping Data

	Open	Enclosed
Length in cm	620	1150
Width in cm	260	320
Height in cm	320	375
Weight in kg	16000	26500

The above performance data are valid as per the following specs:

- Diesel fuel is according to BS2869 class A2 or equivalent
- Lubricating oil is according to API CH4 (SAE 15W/40)
- The coolant should be 50% antifreeze and 50% fresh water

NB: Information above may be changed without prior notice

HEAD OFFICE Power Industry Machineries Company - Lebanon

Beirut - Bir Hassan - Golf Building

Phone: 009611825531 Fax: 009611825532 Mobile: 009611 70 111 277

E-mail: pimco@pimcolb.com Website: www.pimcolb.com

FACTORY

Ghaziyeh - Zahrani Highway

Phone: 00961 1 7 225 226 Fax: 00961 1 7 225 229

