

## CT250 KVA


### Genset Power Output

Name	Voltage	Speed	P.F.	Prime Rating*	Standby rating
CT250	220-380 V	1500-50Hz	0.8	250 kva	275 kva
CT280	220-380 V	1800-60Hz	0.8	284 kva	313 kva

\* The prime power rating of the generating set is for unlimited hours usage with variable load usually between 70% & 80 % of prime rate. Noting that a 10% overload is available for 1 hour every 12 hours operation

### Engine Technical Data

Model	Cummins QSL9G3
Cylinders	6 Vertical In Line
Aspiration	Turbocharged & Aftercooled
Combustion	Direct injection
Cooling system	Water Cooled
Displacement	8.8 L
Lube oil Capacity	26.5 L
Coolant Capacity	15 L
Governor	Electronic
No. of Cycles	4
Speed	1500 rpm
Radiator Cooling Air Flow @ 50Hz	9.4 m <sup>3</sup> /sec



### Alternator Technical Data

Regulation	± 0.5%
International protection	IP23
Insulation class	H
Terminals	12
Frequency	50Hz
Cooling Air Flow @ 50 Hz	0.48 m <sup>3</sup> /sec

### Fuel Consumption (L/Hr)

	50Hz	60Hz
at 100% Load	59.00	70.00
at 75% Load	49.00	58.00
at 50% Load	34.00	41.00
at 25% Load	18.00	21.00

### Genset Shipping Data

	Open	Enclosed
Length in cm	300	395
Width in cm	111	135
Height in cm	190	210
Weight in kg	2050	4100

The above performance data are valid as per the following specs:

- Diesel fuel is according to BS2869 class A2 or equivalent
- Lubricating oil is according to API CH4 ( SAE 15W/40)
- The coolant should be 50% antifreeze and 50% fresh water

NB: Information above may be changed without prior notice

**HEAD OFFICE** Power Industry Machineries Company - Lebanon

Beirut - Bir Hassan - Golf Building

Phone: 009611825531 Fax: 009611825532 Mobile: 009611 70 111 277

E-mail: pimco@pimcolb.com Website: www.pimcolb.com

**FACTORY**

GhaziyeH - Zahrani Highway

Phone: 00961 1 7 225 226 Fax: 00961 1 7 225 229

