

## FPT125 KVA


### Genset Power Output

Name	Voltage	Speed	P.F.	Prime Rating*	Standby rating
FPT125	220-380 V	1500-50Hz	0.8	125	137
FPT140	120-208 V	1800-60Hz	0.8	140	154

\* The prime power rating of the generating set is for unlimited hours usage with variable load usually between 70& 80 % of prime rate. Noting that a 10% overload is available for 1 hour every 12 hours operation

### Engine Technical Data

Model	Iveco -FPT N67SM1
Cylinders	6 Vertical In Line
Aspiration	Turbocharged
Combustion	Direct injection
Cooling system	Water Cooled
Displacement	6.7 L
Lube oil Capacity	17.2 L
Coolant Capacity	25.5 L
Governor	Mechanical
No. of Cycles	4
Speed	1500 rpm
Radiator Cooling Air Flow @ 50Hz	3.2 m <sup>3</sup> /sec



### Alternator Technical Data

Regulation	± 0.5%
International protection	IP23
Insulation class	H
Terminals	12
Frequency	50Hz
Cooling Air Flow @ 50 Hz	0.25 m <sup>3</sup> /sec

### Fuel Consumption (L/Hr)

	50Hz	60Hz
at 110% Load	32.00	38.10
at 100% Load	29.30	34.80
at 80% Load	24.10	28.50
at 50% Load	15.80	19.20

### Genset Shipping Data

	Open	Enclosed
Length in cm	270	340
Width in cm	85	115
Height in cm	155	175
Weight in kg	1,320	2,225

The above performance data are valid as per the following specs:

- Diesel fuel is according to BS2869 class A2 or equivalent
- Lubricating oil is according to API CH4 ( SAE 15W/40)
- The coolant should be 50% antifreez and 50% fresh water

NB: Information above may be changed without prior notice

**HEAD OFFICE** Power Industry Machineries Company - Lebanon

Beirut - Bir Hassan - Golf Building

Phone: 009611825531 Fax: 009611825532 Mobile: 009611 70 111 277

E-mail: pimco@pimcolb.com Website: www.pimcolb.com

**FACTORY**

Ghaziyeh - Zahrani Highway

Phone: 00961 1 7 225 226 Fax: 00961 1 7 225 229

