

## FPT600 KVA

### Genset Power Output

Name	Voltage	Speed	P.F.	Prime Rating*	Standby rating
FPT600	220-380 V	1500-50Hz	0.8	600	660
FPT625	120-208 V	1800-60Hz	0.8	625	685

\* The prime power rating of the generating set is for unlimited hours usage with variable load usually between 70% & 80 % of prime rate. Noting that a 10% overload is available for 1 hour every 12 hours operation

### Engine Technical Data

Model	Iveco -FPT CR16TE1W
Cylinders	6 Vertical In Line
Aspiration	Turbocharged / Intercooled
Combustion	Direct common rail
Cooling system	Water Cooled
Displacement	15.9 L
Lube oil Capacity	38 L
Coolant Capacity	52.5 L
Governor	Electronic
No. of Cycles	4
Speed	1500 rpm
Radiator Cooling Air Flow @ 50Hz	10.53 m <sup>3</sup> /sec



### Alternator Technical Data

Regulation	± 0.5%
International protection	IP23
Insulation class	H
Terminals	12
Frequency	50Hz
Cooling Air Flow @ 50 Hz	0.9 m <sup>3</sup> /sec

### Fuel Consumption (L/Hr)

	50Hz	60Hz
at 110% Load	133.00	143.75
at 100% Load	119.00	129.09
at 80% Load	95.00	103.50
at 50% Load	60.45	66.58

### Genset Shipping Data

	Open	Enclosed
Length in cm	360	523
Width in cm	130	155
Height in cm	210	253
Weight in kg	3,450	5,825

The above performance data are valid as per the following specs:

- Diesel fuel is according to BS2869 class A2 or equivalent
- Lubricating oil is according to API CH4 ( SAE 15W/40)
- The coolant should be 50% antifreeze and 50% fresh water

NB: Information above may be changed without prior notice

**HEAD OFFICE** Power Industry Machineries Company - Lebanon

Beirut - Bir Hassan - Golf Building

Phone: 009611825531 Fax: 009611825532 Mobile: 009611 70 111 277

E-mail: pimco@pimcolb.com Website: www.pimcolb.com

**FACTORY**

Ghaziyeh - Zahrani Highway

Phone: 00961 1 7 225 226 Fax: 00961 1 7 225 229

